# Kodak





## CAPTURE AND SHARE THE JOY.



With the KODAK DC3200 Digital Camera, life has never been easier to capture and share. Get vibrant, eye-catching prints up to 5" x 7" with its 1.0MP resolution. Capture all the important details with its 2X digital zoom. Shoot longer with its 2MB internal memory and COMPACTFLASH Card compatibility. Keep friends and family informed and up-to-date with pictures that look great on e-mail. And see what you shot in an instant with the built-in LCD display. When it comes to capturing fun as it happens, leave it to Kodak – the name you trust in pictures.

#### Easy Sharing

Spread the joy and share your pictures in e-mails and with great-looking prints. With the DC3200, it's easier than ever to stay in touch with friends and family.

#### **Great Pictures**

The DC3200 Digital Camera with its 1.0MP resolution makes great prints up to 5" x 7".

#### **Get Close**

With the DC3200's 2X digital zoom, you can get the shot you want with the touch of a button.

#### Internal Memory

You won't miss a shot. With its 2MB internal memory and COMPACTFLASH Card compatibility, you can keep shooting longer.

#### **Preview and Review Your Pictures**

See what you shot in an instant with the built-in LCD screen. With the DC3200, you'll know if the picture is a keeper.





\*Simulated LCD image

### KODAK DC3200 Digital Camera

#### **SPECIFICATIONS**

CCD RESOLUTION	I.2 megapixel I280x960	ISO E
IMAGE RESOLUTION   52x864 (high	I.0 megapixel ), 576x432 (standard)	LCD
IMAGE QUALITY SETTINGS Best, better, good		FLAS
	MB internal memory, ASH Card compatible	FILE
VIEWFINDER	Optical viewfinder	VIDE
LENS (39 mm = 3.	5.4 mm f/3.6 5 mm film equivalent)	SPEC
DIGITAL ZOOM	2X	INTE POW
FOCUSING	Fixed	DIME
FOCUS DISTANCE Normal: 0.	Normal: 0.6m (2 feet) to infinity	
EXPOSURE CONTROL	Auto	CERT
WHITE BALANCE	Auto, daylight, fluorescent, tungsten	WEIC
SHUTTER SPEED	1/4 to 1/500 second	WAR
APERTURE RANGE	Auto (f/3.6, f/8)	

ISO EQUIVALI	ENT 100
LCD	40.64 mm (1.6 inches) color review/preview display
FLASH	l.5-2.4m (5-8 ft) (automatic, fill, off)
FILE FORMAT	JPEG
VIDEO OUT	NTSC only (US) NTSC/PAL (Canada)
SPECIAL EFFE	DPOF
INTERFACE	Serial
POWER	4 AA alkaline batteries (included)
DIMENSIONS	WxDxH (mm) 113x81x53.4 WxDxH (inches) 4.45x3.19x2.1
CERTIFICATIO	FCC,VCCI
WEIGHT	Without batteries (grams): 215 Without batteries (ounces): 7.6
WARRANTY	One year

ORDERING INFORMATION	CAT. NO.
KODAK DC3200 Digital Camera (US)	194-0063
KODAK DC3200 Digital Camera (Canada)	830-6128
RECOMMENDED ACCESSORIES	
KODAK Picture Card, 16MB	826-6330
KODAK USB Picture Card Reader	136-1765
KODAK Digital Camera AC Adapter, 7 Volt	122-0557
KODAK Rapid Charger with 4 AA Rechargeable Ni-MH Batteries	889-0535
Video Out Cable	181-7774
Lens Cap	112-4353
Digital Camera Bonus Pack	851-7336
Color Accent Bag (blueberry)	122-0482
Color Accent Bag (grape)	175-2567

KODAK Accessories help make this great camera even better. See your local retailer or visit us at www.kodak.com/go/shop

#### SYSTEM REQUIREMENTS

WINDOWS SYSTEMS

WINDOWS 95, 98, 98SE, or WINDOWS 2000 Personal computer with PENTIUM 90 MHz or greater microprocessor 32MB RAM or greater (64MB for WINDOWS 2000) 100MB hard drive disk space or greater recommended CD-ROM drive Available serial port Color monitor with 256 colors (16 or 24-bit color recommended)



For more information on the DC3200 Digital Camera, visit www.kodak.com/go/dc3200

<u>USD</u>¶ª UNIVERSAL SERIAL BUS

#### Easy to use. Easy to e-mail.









#### PACKAGE CONTENTS

- KODAK DC3200 Digital Camera
- Wrist strap
- KODAK Software CD
- Serial cable
- 4 AA alkaline batteries
- Documentation kit



Order long-lasting, photo-quality prints of your digital pictures online.

Images are representative of video visuals, not actual video images.



IC-865 CAT No. 129-0329

Mouse

© 2000 Eastman Kodak Company. Kodak, Take Pictures. Further., and the Kodak Picture Friendly logo are trademarks.

TAKE PICTURES. FURTHER.